

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB000014D
Revision No:
1

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

That the Primary deck coverings

with type designation(s)
Sikafloor® Marine-504

Issued to

Sika Services AG
Zürich, ZH, Switzerland

is found to comply with the requirements in the following Regulations/Standards:

Regulation (EU) 2020/1170,

item No. MED/3.1. SOLAS 74 as amended, Regulation II-2/4, II-2/6 & X/3, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2026-08-09**.

Issued at **Høvik** on **2021-08-10**

DNV local station:
Augsburg

Approval Engineer:
Tessa Bieber



Notified Body
No.: **0575**

for **DNV AS**

Sverre Olav Bergli
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

“Sikafloor® Marine-504”

is a two-component polyurethane water based matt seal coat.

This certificate covers the following four (4) application options:

1. Sikafloor Marine 504 – ‘Pure’

Application: one layer Sikafloor Marine 504, 320 gram/m²
Maximum total thickness: Approx. 0,25 mm

2. Sikafloor Marine 504 with anti-slip layer

Application (seen from exposed side): - one layer Sikafloor Marine 504, 320 gram/m²
- one layer anti slip, 80 gram/m²
- one layer Sikafloor Marine 504, 320 gram/m²
Maximum total thickness: Approx. 0.5 mm

3. Sikafloor Marine 504 with color flakes/ chips

Application (seen from exposed side): - one layer Sikafloor Marine 504, 320 gram/m²
- one layer color flakes/chips, 80 gram/m²
- one layer Sikafloor Marine 504, 320 gram/m²
Maximum total thickness: Approx. 0.5 mm

4. Sikafloor Marine 504 with color flakes/ chips and an anti-slip layer

Application (seen from exposed side) - one layer Sikafloor Marine 504, 320 gram/m²
- one layer color flakes/chips 80 gram/m² + one layer anti slip, 80 gram/m²
- one layer Sikafloor Marine 504, 320 gram/m²
Maximum total thickness: Approx. 0.5 mm

Application/Limitation

Primary deck covering, not generating excessive quantities of smoke nor toxic products in fire.

The product may be applied over any steel or non-combustible material.

Sikafloor Marine 504 – ‘Pure’

Approved colour: Transparent
Max. organic content: 53%

Sikafloor Marine 504 with anti-slip layer

Approved colour: Transparent
Max. organic content: 53%

Sikafloor Marine 504 with color flakes/ chips

Approved colour: Transparent
Max. organic content: 53%

Sikafloor Marine 504 with color flakes/ chips and an anti-slip layer

Approved colour: Transparent
Max. organic content: 53%

Not to be used as an integrated part of horizontal class A division unless tested as such.

The product may also be used as floor covering in accordance with IMO 2010 FTP code Part 5 appendix 4 paragraph 4.9.2.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test report PFB10436E dated 2020-11-13 from DBI, Hvidovre, Denmark

Test report PFB10436B dated 2020-11-13 from DBI, Hvidovre, Denmark



Job Id: **344.1-005515-3**
Certificate No: **MEDB000014D**
Revision No: **1**

Tests carried out

Tested according to IMO 2010 FTP Code Part 5 and Annex 2, item 2.2.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, MED Mark of Conformity and USCG approval if applicable (see page 1).