

Product specification sheet



- **Profile type:**

2505



- **Type:** 2505
- **Description:** slip-resistant insert with expansion joints
- **Application:** changeable insert for stair the nosing profiles 700, 701, 702 703, 704, 705, 706 , 707, 708 an 709 manufactured from aluminium and brass
- **Length of the roll :** 25 m
- **Width of the profile:** 29,0 mm
- **tolerance:** + 0,3 mm
- **colours:** black (F100), brown (F130), anthracite (F140), light grey (F142), beige grey (F143), beige (F149), blue (F169), gree (F184*), red (F189), yellow (F190) und photoluminescet (F200)

* discontinued items
- **Anti-Slip property** Factor R9
- **fire protection class:** **B2 not dripping**

Product specification sheet



- **Instruction for Installation:**

The trimming and working up should be carried out after heating to room temperature (approx. 7 – 22°) to minimize afterward extension or shrinking.

Due to the longitudinal groove on the bottom side of the PVC-insert it is possible to compress it and to press it into dovetail guide of the metal profile without effort (please do not trim the PVC-insert in inserted condition).

The insert has to be glued punctiformly and at the ends, to minimize possible shrinking, in particular at the bevel cuts.

The PVC-insert should be transported and stored protected.

The indicated data are typical or average values, but are not assured attributes. This product is not subject to the Construction Products Regulation.

Technical data:

Insert-Characteristics	Carrier Material
Material	PVC-P / Soft-PVC
Base weight	132 g/m 185 g/m
Tear strength	16,2 N/mm ²
	ISO 527
Colour	Black, brown, anthracite, light grey, beige grey, blue, green, red, yellow and photoluminescent
Breaking strength in %	315 %